

SmartTerminal ST-1210



Models may vary from the image shown

Read chipcards with one hand!

Marginally bigger than the chipcard itself, the device is discrete and can be operated with one hand.

Key benefits

- Smart card reader with USB interface
- USB 2.0-compatible
- One-handed operation through functional design and stable construction
- PC/SC Smart card reader
- CT-API and OCF support
- Protocols: T=0, T=1, S=8, S=9, S=10
- CCID compatible
- EMV 2000 Level 1 approved

Technical Data:

Housing colour:

Product dependant, see table "Models"

Weight (product):

approx. 90 g

Cable Length:

approx. 1.75 m

Storage Temperature:

-20°C to 60°C

Operating Temperature:

0°C to 50°C








Current Consumption:

max. 100 mA

Interface:

- USB

Product approvals:

- cURus 
- VDE GS 
- c-tick 
- GOST-R 
- CE 
- FCC 
- FIPS 201 

System requirements:

- USB connection

Dimensions (product):

approx. 105 x 70 x 12 mm

Packaging dimensions:

approx. 145 x 90 x 35 mm

Packaging (version):

Product dependant, see table "Models"

Smartcard-Reader:

- Hardware interface: USB
- Agency Approvals: EMV 2000 Level 1
- Chip-card protocols: T=0, T=1, S=8, S=9, S=10
- Contact: mechanical swipe reader
- Software interface: CT-API, PC/SC, CCID, OCF
- Mating cycles: approx. 100,000 operations
- Compatible chip card types: Reads and writes on all ISO 7816 cards
- Transmission speed reader <==> card: 412,903 Bit/s
- Transmission speed reader <==> system: max. 12 MBit/s
- Chip card pulse frequency: 4.8 MHz

Packaging Unit:

- Number of products in the master package: Product dependant, see table "Models"
- Number of master packages per pallet: Product dependant, see table "Models"

Warranty:

2 years

Errors, technical changes and delivery possibilities excepted. Technical information refers only to the specifications of the products. Features may differ from the information provided.

Models:

	Product name	Order number	Housing colour	Packaging (version)	Number of products in the master package	Number of master packages per pallet
1	SmartTerminal ST-1210	ST-1210UAE	black	Collective packaging	250	8
2	SmartTerminal ST-1210	ST-1210UAE-W	black	White box	219	6
3	SmartTerminal ST-1210	ST-1210UAF	light gray	Collective packaging	250	8
4	SmartTerminal ST-1210	ST-1210UAF-W	light gray	White box	219	6
5	SmartTerminal ST-1210	ST-1210UBE-R	black	Pretty box	40	12
6	SmartTerminal ST-1210	ST-1210UDE-R	black	Pretty box	40	12
7	SmartTerminal ST-1210	ST-1210UEE-R	black	Pretty box	40	12