

=8G

OT-15T



DOSMAR OT-15T Touch Monitor

The cost effective touch monitor with sturdy and robust base what prevents shaking within touch operations, spill and dust proof design in front bezel, ideal for retail and hospitality environment.

OT-15T has universal compatibility since combined with both VGA and DVI video inputs, also as well with combo touch interface RS232 and USB, moreover it has 2 x USB HUB for peripheral devices.

Specifications

Display Size: 15"

Active Area: 304.1 x 228 mm

Optimal Resolution: 1024 x 768

Brightness: 250 nits (typ)

Contrast Ratio: 600:1(typ)

Response Time: 8 ms (typ)

LCD Viewing Angle: (L/R/U/D) 80/80/80/80

Input Video: VGA (D-Sub 15 Pins) and DVI-D (Dual Link)

Power consumption: 20W

Input Frequency:

Horizontal: 31.5-60.2 kHz

Vertical : 56.3Hz-75Hz

Power supply: DC 12V +/- 10%

Touch Technology: 5-Wire Resistive

Touch Interface: Combo RS232 and USB

Temperature:

Operating: 0~40 degr. C

Storage: -10~50 degr. C

Weight: 4.67kgs (Net)

Size: 365.2(W) x 338.6(H) x 200(D) mm

Approvals: CE/FCC/BSMI/CCC

Options

- MCR module, triple tracks, USB
- VFD module, 2x20 chars, USB
- 2-nd rear LCD: 7", 8", 8,4", 10,4", VGA or USB

* Product specification can be changed without prior notice

Features



Screen tilting angle freely up to 90 degrees

Detachable MCR module

Spill and dust proof design in front bezel

OSD control buttons in bezel bottom



Optional choices of second displays for advertising purposes:

- 2x20 chars VFD
- 7" WVGA LCD
- 8.4" SVGA LCD
- 10.4 SVGA LCD



Wide compatibility:

- VGA and DVI ports for video signal
- COM and USB port for touch interface
- 2 x USB hub
- 1 x COM(RJ45) port for peripheral devices.



Sturdy and robust base with metal bottom

Through stand cabling design reduces disordered cables

Hidden in base AC/DC power adaptor for space saving

Dimensions

